KNIPEX TubiX® XL – Pipe Cutter

The perfect cut for larger pipes with QuickLock mechanism

Quickly and precisely cuts large diameters of metal pipes between \emptyset 6 and 76 mm (1/4"-3")



KNIPEX TubiX® XL

Pipe Cutter

Significantly easier pipe cutting due to the combination of the QuickLock mechanism and guide rollers with needle-bearings

- ► Spring-loaded QuickLock mechanism holds the tool on the pipe once locked in place
- ► Precise and quick: exact positioning of the cutting wheel on the pipe
- ► High-quality needle-bearings enable the cutting wheel and four guide rollers to cut with ease
- > Cuts pipes from Ø 6-76 mm (1/4"-3") and a wall thickness up to 2 mm
- > Cutting wheel made of high-grade ball-bearing steel
- > Quick replacement of the cutting wheel without any tools needed spare cutting wheel stored in the handle
- > Lightweight and durable aluminium housing
- > Removable, precision-ground deburring tool
- > For plumbing, heating and air conditioning: easily cut gas and water pipes made of copper, brass and stainless steel
- > For the electrical trade: cuts rigid steel conduits and for stripping steel wire armoured cables



The spring-loaded cutting wheel keeps the KNIPEX TubiX® XL in place and prevents slipping.



In one easy step, the KNIPEX TubiX® XL can be positioned quickly and precisely on all pipes with a diameter between 6 and 76 mm.



The precisely ground deburring tool can be taken out of the tool when needed.



A spare cutting wheel is stored in the blue handle for quick replacement.



Information on the smaller
KNIPEX TubiX® for pipes up to 35 mm:
www.knipex.com/tubix

	EAN	←→			7,7
Article no.	4003773-	mm	Ø mm	Ø Inch	g
90 31 03 BK	088127	ca. 256	6 – 76	1/4 – 3	950
90 31 03 E01	Deburring tool for KNIPEX TubiX® XL 90 31 03				7
90 39 02 V01 085874 Cutting wheel for stainless steel and copper for KNIPEX TubiX® 90 31 02 and KNIPEX TubiX® XL 90 31 03					8
90 39 02 V03 086307 5 x Cutting wheel for stainless steel and copper for KNIPEX TubiX® 90 31 02 and KNIPEX TubiX® XL 90 31 03				25	

For cutting copper, brass and stainless steel pipes with a wall thickness up to 2 mm and diameters from 6 to 76 mm (1/4"-3").